

INFO

Anwendung Entkopplung



		protect Vlies	protect grid	protect sound 13 dB	protect sound 13 dB	protect sound 14 dB	protect 14 dB	protect 17 dB	protect 18 dB	protect fast II	protect plus	protect drain direkt	protect drain
Boden Innenbereich	Zementestrich unbeheizt	●	●	●	●	●	●	●	●	●	●		
	Zementestrich beheizt	●	●	●			●	●	●	●	●		
	Beton	●	●	●	●	●	●	●	●	●	●		
	Calciumsulfat-/Anhydritestrich unbeheizt	●	●	●	●	●	●	●	●	●	●		
	Calciumsulfat-/Anhydritestrich beheizt	●	●	●	●	●	●	●	●	●	●		
	Gussasphaltestrich	●	●	●	●	●	●	●	●	●	●		
	Magnesia- und Steinholzestrich	●	●	●	●	●	●	●	●	●	●		
	Terrazzo	●	●	●	●	●	●	●	●	●	●		
	fester Fliesenbelag / Naturstein	●	●	●	●	●	●	●	●	●	●		
	Holzdielen	●	●	●	●	●	●	●	●	●	●		
	Parkett verklebt	●	●	●	●	●	●	●	●	●	●		
	V100-Spanplatten	●	●	●	●	●	●	●	●	●	●		
	OSB-Platten	●	●	●	●	●	●	●	●	●	●		
	Trockenestrichelemente	●	●	●	●	●	●	●	●	●	●		
Boden Außenbereich	Zementestrich		●*							●	●	●	●
	Beton		●*							●	●	●	●
	Betonwerkstein, Terrazzo		●*							●	●	●	●
	Naturstein		●*							●	●	●	●
	fester Fliesenbelag		●*							●	●	●	●
Dämmwert bis zu	-	-	13 dB	13 dB	14 dB	14 dB	17 dB	18 dB	-	-	-	-	
Stärke in mm	0,7	0,5	4,0	9,0	15,0	1,3	3,0	2,0	3,0	1,1	5,0	9,0	

* unter Verbundabdichtungen